



IKO enertherm ALU

R_D-waarden en verpakkingseenheid per dikte:

Dikte (mm) R _d (m ² .K/W)		30 1,35	40 1,80	50 2,25	60 2,70	70 3,15	75 3,40	80 3,60	82 3,70	85 3,85	90 4,05	100 4,50	110 5,00	120 5,45	130 5,90	132 6,00	140 6,35	150 6,80	160 7,25	180 8,15	200 9,05
1 200 x 600	m2/pak	11,52	8,64	7,20	5,76	5,04	-	4,32	-	-	2,88	3,60	-	2,88	-	-	2,16	-	1,44	1,44	1,44
	m2/pal	115,20	86,40	72,00	57,60	50,40	-	43,20	-	-	40,32	36,00	-	28,80	-	-	25,92	-	23,04	20,76	17,28
1200 x 600 TG	m2/pak	-	8,64	7,2	5,76	5,04	-	4,32	-	-	2,88	3,60	-	2,88	-	2,16	2,16	1,44	1,44	-	-
	m2/pal	-	86,40	72,00	57,60	50,40	-	43,20	-	-	40,32	36,00	-	28,80	-	25,92	25,92	23,04	23,04	-	-
1 200 x 1 000	m2/pak	-	-	-	9,60	8,40	-	7,20	-	-	-	6,00	-	4,80	-	-	3,60	-	-	-	-
	m2/pal	-	-	-	48,00	42,00	-	36,00	-	-	-	30,00	-	24,00	-	-	21,60	-	-	-	-
2 400 x 1 200	m2/pak	46,08	34,56	28,80	23,04	20,16	-	17,28	-	14,40	11,52	14,40	11,52	11,52	-	-	8,64	5,76	-	-	-
	m2/pal	230,40	172,80	144,00	115,20	100,80	-	86,40	-	86,40	70,64	72,00	57,60	57,60	-	-	57,60	46,08	-	-	-